





NEC's UNIVERGE SIP Desktop Phones provide all the features and functionality of traditional phones with the seamless integration of advanced IP applications. Voice & data integration is no longer limited to the network or the PC desktop; it is now in the end-users' hands.

MULTICOLOUR LAMP

7-Colour customisable indicator controlled by XML application.

DIRECTORIES

Quickly look up contacts in the directory by using the alphabetic keyboard.

HD AUDIO QUALITY

Both speakerphone and handset offer super wideband technology for superior HD audio quality.

ADJUSTABLE STAND

5 adjustments – Built-in wall mount.

HIGH-QUALITY HANDSET

The slim line handset increases the conversation comfort.

INTUITIVE & INTERACTIVE NAVIGATION

All models offer intuitive and interactive navigation of NEC's advanced communications features. Interactive keys or touch: The choice is yours.

HOTDESKING

Allows handsets and desk space to be shared by a number of employees, helping keep costs down.

SECURITY

TLS and SRTP security encryption technology to protect calls and accounts.

POWER OVER ETHERNET (PoE)

To power the device and give it a network connection.

FLEXIBILITY WITH ADD-ON MODULES

Add functions and direct-dial buttons. 60 additional line keys turn your phone into a switchboard.





www.univergeblue.com



eatures	Model	DT920S	DT920S	DT930S		
Characteristics	Version	6 button	Self-labelling	Touch Panel		
	Colour	Black				
	Dimension (W×H×D) mm	181x243x133				
	Weight (kg)	0,8 kg	0,9 kg	0,9 kg		
	Power Feeding	PoE Class 1 (3.6W)	PoE Class 1 (3.75W)	POE Class 2 (4.32W) AC Adapter (Local)		
djustable stand	Tilt Angle	✓ 5 Steps (25°, 32°, 39°, 46°, 55	 °)	/ le / le / le		
LCD Display	LCD	Monochrome; 168x41 (dots)	3.5 inch Colour Resolution 320 x 240	4.3"; Colour (TFT Type) Resolution 480x272		
	LCD Backlit	✓				
	Home Screen UI	Classic Mode	Portal Mode	Portal Mode		
	Screen Saver	-	✓	 ✓ 		
	Turn Off Display	✓				
Kevs	Ten Key Backlit					
	Soft Key	 ✓ (4 keys) ✓ (4 keys on panel) 				
	Programmable Key	6	32			
	Cursor Key	✓ ✓	1	No		
ML browser	Display Text and Image	✓ ·		l		
(XML Open	LED Control	 ✓ ✓ 				
terface)	Photo Frame	No				
	Push	✓ · · · · · · · · · · · · · · · · · · ·				
	RTP Streaming	✓ · · · · · · · · · · · · · · · · · · ·				
coming Call Lamp	MWILED	Standard Size, 3 colours (red, green, yellow)	Wide size, 7 colours (red, green, blue, yellow, cya	an, magenta, white)		
letwork	LAN	2-Port, 10BASET/100BASETX/1000BASE-T, Full-Duplex/Half-Duplex, Auto Negotiation/ Fixed (Except 1000BASE-T)				
	IP Addressing	Sets via DHCP Server/Sets Statically				
	QoS	ToS (IP Precedence, Diffserv)				
	Support IP Version	IPv4/IPv6				
	DHCP	✓				
	Tag VLAN	✓				
	PC Port VLAN	✓ · · · · · · · · · · · · · · · · · · ·				
	VPN	✓ (L2TP/IPsec)				
	802.1X	EAP-TLS/EAP-MD5				
	Security	SIP/RTP encryption				
	LAN Port Speed	10/100/1000Mbps				
	PC Port Speed	10/100/1000Mbps				
LCD Display Keys XML browser (XML Open interface) Incoming Call Lamp Network Connections Call Sound	Bluetooth Headset	-		✓		
	Bottom Option	-				
	Side Option	-		✓ (DSS)		
	Headset Jack	 - (USS) ✓ (RJ9) 				
Call	Personal Directory	 ✓ ((07)) 				
	System Directory	 ✓ ✓ 				
	Call History	 ✓ ✓ 				
Sound	Download Ringtone	 ✓ ✓ 				
	Handset	Wide Band (inc. G722 CODEC)				
	Handsfree	Full Duplex				
	Handstree Hold Music	Full Duplex				
Optional Support	Gigabit Ethernet					
	Wired Headset					
	Electronic Hook Switch (EHS)					

Ø 6 8 5



DT900S SIP I	DESKTOP PHONES					
Features	Model	DT920S	DT920S	DT930S		
Maintenance	Auto-Configuration	✓				
	Network Management	✓				
Standards	Electrical	EN 55022, EN 55024 Class B				
	ROHS	All Models are ROHS Compliant				
	Safety	UL/CSA 60950				
Environmental	Operating Conditions	Temperature Range: 0 to 40	Temperature Range: 0 to 40° C, Humidity: 10 to 90% RH (Not Condensing)			
	Storage	Ambient Temperature Range	Ambient Temperature Range: -20 to 60° C, Ambient Humidity: 10 to 90% RH			



DT920S - 6-button



DT920S - Self-labelling



DT930S - Touch panel



```
60-line DSS Console
```



Touch panel phone with 60-line DSS Console

NEC and the NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with © or TM are registered trademarks of their respective owners. Models may vary for each country, and due to continuous improvements this specification is subject to change without notice. Please refer to your local NEC representative(s) for further details.

EMEA (Europe, Middle East, Africa) NEC Enterprise Solutions www.nec-enterprise.com

For further information please contact NEC Enterprise Solutions or:

TELECOM GROUP

Turnkey Telecom Group 3 St Peters Court, Middleborough, TURNKEY Colchester, Essex CO1 1WD Tel: 0333 003 5700 enquiry@turnkeytele.com www.turnkeytele.com

